



FLUSH FACE QUICK DISCONNECT

The CTP new Flush Face Quick Disconnects offer leak free performance in high-pressure environments and other applications. They are made from carbon steel and are zinc plated to keep from corrosion.

Some additional features include:

- ✓ *Safety lock to help prevent from accidental disconnection*
- ✓ *Fitted seal to provide minimal or no inclusion of contaminants during connection*
- ✓ *Their flat face design prevents fluid loss while disconnected*
- ✓ *Bidirectional flow*
- ✓ *Ease to clean*

The most popular applications for the Quick disconnects (couplers) are:

- ✓ *Hammer circuits*
- ✓ *High-pressure pulse applications*
- ✓ *Leak free environments*
- ✓ *Construction, mining and agricultural industries*

Part No.	Coupler Size	Thread Size	Type
1060401	19	1-5/16-12	Female
1060406	19	1-5/16-12	Male
1532994	12	7/8-14	Female
1532995	12	7/8-14	Male
1938334	12	1-14	Male
1938335	12	1-14	Female
1956525	12	1-1/16 - 12	Female
1956526	12	1-1/16 - 12	Male
2416189	12	Bulkhead	Male

*Other part no. not included in the list are available. Please contact your sales representative if you have any questions. Part Numbers are used for reference purposes only